



Three-phase synchronous self-regulated brushes 2 and 4 poles alternators. Protection: IP21. Standard voltage: 240/416 V - 60 Hz. Short circuit current: greater than 3.5 In. STYLE: B3/B14, IM B35 (B3/B9), IM B35-J609b, SAE 3, SAE 4, SAE 5.

| Technical characteristics 2 pole | | | | | | | | | |
|----------------------------------|--------------|---------------------|------------------|---------------------|---------------------|------------------|---------------------|------------------|---------------|
| TYPE | CODE | 50 Hz - 3000 r.p.m. | | | 60 Hz - 3600 r.p.m. | | | WEIB | |
| | | POWER | | cos =0.8 Eff.(%) | POWER | | cos =0.8 Eff.(%) | B 35/B34 (kg) | B2SAE (kg) |
| | | (kVA) | cos =0.8 (kW) | | (kVA) | cos =0.8 (kW) | | | |
| GS 140 M T2 A | 80306145.X 2 | 22 | 18 | 83 | 27.5 | 22 | 84 | 76 | 92 |
| GS 140 M T2 B | 80306170.X 2 | 27 | 21.6 | 85 | 34 | 27 | 86 | 86 | 102 |
| GS 140 L T2 A | 80306210.X 2 | 31.5 | 25.2 | 86 | 40 | 31.5 | 87 | 101 | 117 |
| GS 140 L T2 B | 80306260.X 2 | 38 | 30.4 | 88 | 47.5 | 38 | 89 | 122 | 138 |

| Technical characteristics 4 poles | | | | | | | | | |
|-----------------------------------|----------------|---------------------|------|----|---------------------|------|----|-----|-----|
| | | 50 Hz - 1500 r.p.m. | | | 60 Hz - 1800 r.p.m. | | | | |
| | | | | | | | | | |
| GGS 140 M T4 B | 80304170.X 2 | 16 | 12.8 | 82 | 20 | 16 | 83 | 88 | 104 |
| GGS 140 L T4 A | 80304240.X 2 | 22.5 | 18 | 84 | 28 | 22.5 | 85 | 115 | 131 |
| GGS 140 L T4 B | 80304265.X 2 | 27 | 21.6 | 85 | 34 | 27 | 86 | 125 | 141 |
| GGS 140 L LT4C | 80304265.X 220 | 30 | 24 | 86 | 41 | 32 | 87 | 127 | 143 |

* Only in SAE 3